ASUS ESC8000-E11 Rack (4U) Grau





Marke : ASUS

Artikel-Code: 90SF02I1-M003D0

Produktname : ESC8000-E11

ASUS ESC8000-E11. Prozessorhersteller: Intel, Prozessorfamilie: Skalierbare Intel® Xeon®, Kompatible Prozessoren: Intel® Xeon®. Unterstützte Arbeitsspeicher: DDR5-SDRAM, Unterstützte DIMM-Modulkapazitäten: 16GB, 32GB, 64GB, 128GB, 256GB, RAM-Speicher maximal: 6 TB. unterstützte Speicherlaufwerksgrößen: 2.5,3.5,M.2, Unterstützte Speicherlaufwerke: HDD & SSD, SSD-Formfaktor: M.2. Gehäusetyp: Rack (4U), Produktfarbe: Grau. AC Eingangsspannung: 220 - 240 V, AC Eingangsfrequenz: 50/60 Hz, Eingangsstrom: 15.5 A

Prozessor	
Prozessorhersteller	Intel
Prozessorfamilie	Skalierbare Intel® Xeon®
Anzahl unterstützter Prozessoren *	2
Kompatible Prozessoren	Intel® Xeon®
Speicher	
Zahl der DIMM Slots *	32
Unterstützte Arbeitsspeicher *	DDR5-SDRAM
Unterstützte DIMM-Modulkapazitäten	16GB, 32GB, 64GB, 128GB, 256GB
RAM-Speicher maximal	6 TB
Unterstützte RDIMM Taktraten	4400 MHz
Speichermedium	
Anzahl der unterstützten Speicherlaufwerke *	9
HDD Laufwerkschächte Hot-Swap *	✔
Anzahl der 2,5" Erweiterungseinschübe	8
Anzahl der 3,5" Erweiterungseinschübe	8
unterstützte Speicherlaufwerksgrößen	2.5,3.5,M.2
Unterstützte Speicherlaufwerke	HDD & SSD
SSD-Formfaktor	M.2
Anschlüsse und Schnittstellen	
USB 3.2 Gen 1 (3.1 Gen 1) Anzahl der Anschlüsse vom Typ A	2
Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	2
IPMI LAN (RJ-45)-Anschluss	✔

Anschlüsse und Schnittstellen	
Anzahl VGA (D-Sub) Anschlüsse	1
Anzahl COM-Anschlüsse	1
Erweiterungssteckplätze	
PCI-Express-Slots-Version	5.0
Technische Details	
Konformitätsbescheinigungen	BSMI, CB, CE, Eidgenössische Kommunikationskommission (FCC), RCM
Design	
Gehäusetyp *	Rack (4U)
Produktfarbe	Grau
LED-Anzeigen	✔
Ein-/Ausschalter	✔
Reset-Knopf	✔
Energie	
Unterstützung für redundantes Netzteil	✔
AC Eingangsspannung	220 - 240 V
AC Eingangsfrequenz	50/60 Hz
Eingangsstrom	15.5 A
80 Plus Zertifizierung	80 PLUS Titanium
Betriebsbedingungen	
Betriebstemperatur	10 - 35 °C
Temperaturbereich bei Lagerung	-40 - 70 °C
Luftfeuchtigkeit bei Lagerung	20 - 90%
Gewicht und Abmessungen	
Breite	440 mm
Tiefe	800 mm
Höhe	174,5 mm
Gewicht	27 kg
Verpackungsdaten	
Paketgewicht	52 kg

4711387206324

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 21-NOV-2026. Prints or copies of Information are only valid on the printed Publication date