APC DIN-Schienen-USV für Schalttafelmontage, ohne Batterie, 500 VA, 230 V



Marke : APC

Artikel-Code: SUA500PDRI

Produktname : APC DIN-Schienen-USV für Schalttafelmontage, ohne Batterie, 500 VA, 230 V

APC DIN-Schienen-USV für Schalttafelmontage, ohne Batterie, 500 VA, 230 V

APC DIN-Schienen-USV für Schalttafelmontage, ohne Batterie, 500 VA, 230 V:

Bewährte USV-Systeme für Steuerungsanwendungen und widrige Umgebungsbedingungen. Nicht zur Verwendung bei Privatkunden geeignet.
APC DIN-Schienen-USV für Schalttafelmontage, ohne Batterie, 500 VA, 230 V. USV-Topologie: Line-Interaktiv, Ausgangskapazität: 0,5 kVA, Ausgangsleistung: 325 W. AC-Steckertypen: Hard Wire 5-wire (3PH + N + G). Formfaktor: Rackmount, Produktfarbe: Schwarz. Konformitätsbescheinigungen: RoHS, Zertifizierung: CE, VDE. Breite: 362 mm, Tiefe: 171 mm, Höhe: 148 mm

Merkmale	
USV-Topologie *	Line-Interaktiv
Ausgangskapazität *	0,5 kVA
Ausgangsleistung *	325 W
Eingangs-Betriebsspannung (min) *	151 V
Eingangs-Betriebsspannung (max) *	302 V
Eingangsfrequenz *	47/53 Hz
Ausgangs-Betriebsspannung (min)	220 V
Ausgangs-Betriebsspannung (max)	240 V
Anstieg der Energiemenge	540 J
Effizienz	94%
Ausgangsspannung Gesamtverzerrungsfaktor THD	5%
Geräuschpegel	55 dB
Druckanstiegsschutz	✔

Anschlüsse und Schnittstellen	
AC-Steckertypen	Hard Wire 5-wire (3PH + N + G)
Anzahl der AC-Ausgänge	0 AC-Ausgänge
RS-232 port	1

Akku/Batterie	
Anzahl unterstützter Akkus/Batterien	1

Design	
Formfaktor *	Rackmount

Design	
Produktfarbe *	Schwarz

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-15 - 45 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Luftfeuchtigkeit bei Lagerung	0 - 95%
Höhe bei Betrieb	0 - 3000 m
Höhe bei Lagerung	0 - 15000 m

Zertifikate	
Konformitätsbescheinigungen	RoHS
Zertifizierung	CE, VDE

Lieferumfang	
Betriebsanleitung	✔

Gewicht und Abmessungen	
Breite	362 mm
Tiefe	171 mm
Höhe	148 mm

Verpackungsdaten	
Verpackungsbreite	297 mm
Verpackungstiefe	481 mm
Verpackungshöhe	297 mm

Logistikdaten	
Warentarifnummer (HS)	85078000
Gesamter Kohlendioxid-Fußabdruck (kg of CO2e)	441,6

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 21-NOV-2026. Prints or copies of Information are only valid on the printed Publication date