APC Easy Rack PDU, Ausgang mit Messfunktion, 0 HE, 3-phasig, 11kW, 230V, 16A, (18) C13 und (6) C19 Ausgänge, IEC60309 3P+N+PE Eingang



Marke : APC

Artikel-Code: EPDU2216MBO

Produktname : Easy Rack PDU, Ausgang mit Messfunktion, 0 HE, 3-phasig, 11kW, 230V, 16A, (18) C13 und (6) C19 Ausgänge, IEC60309 3P+N+PE Eingang

Easy Rack PDU, Ausgang mit Messfunktion, 0 HE, 3-phasig, 11kW, 230V, 16A, (18) C13 und (6) C19 Ausgänge, IEC60309 3P+N+PE Eingang
APC Easy Rack PDU, Ausgang mit Messfunktion, 0 HE, 3-phasig, 11kW, 230V, 16A, (18) C13 und (6) C19 Ausgänge, IEC60309 3P+N+PE Eingang. PDU-Typen: Messgerät, Rack-Kapazität: 0U, Typ: Dreiphasig. Anzahl der AC-Ausgänge: 16 AC-Ausgänge, AC-Steckertypen: C13-Koppler, C19-Koppler, Stecker: C13-Koppler. Kabellänge: 3 m. Überwachung: Strom, Leistung, Spannung. Nominale Eingang Spannung: 400 V, Stromstärke (maximal): 16 A, AC Eingangsfrequenz: 50/60 Hz

Design	
PDU-Typen *	Messgerät
Typ	Dreiphasig
Rack-Kapazität *	0U
Montage	Senkrecht
Gehäusematerial	Aluminium
Produktfarbe	Schwarz
Display	LCD
Ein-/Ausschalter	✗

Anschlüsse und Schnittstellen	
Anzahl der AC-Ausgänge *	16 AC-Ausgänge
Stecker	C13-Koppler
AC-Steckertypen *	C13-Koppler, C19-Koppler

Merkmale	
Verkettung	✗
Reset-Knopf	✓
LED-Anzeigen	✓
Kabellänge	3 m

Management-Funktionen	
Überwachung	Strom, Leistung, Spannung

Energie	
Nominale Eingang Spannung *	400 V
AC Eingangsfrequenz	50/60 Hz
Stromstärke (maximal) *	16 A
Nominale Ausgang Spannung	230 V
Ausgangsspannung	230 V

Energie	
Ladekapazität	11000 VA
Anzahl der Phasen	3
Max. Leistung	11000 W

Zertifikate	
Konformitätsbescheinigungen	CE, RCM, REACH, RoHS, cTUVus, UKCA
Zertifizierung	CE, TUV, EN 62368-1, RCM, UKCA

Betriebsbedingungen	
Betriebstemperatur	-5 - 50 °C
Temperaturbereich bei Lagerung	-25 - 65 °C
Relative Luftfeuchtigkeit in Betrieb	5 - 95%
Luftfeuchtigkeit bei Lagerung	5 - 95%
Höhe bei Betrieb	0 - 3000 m
Höhe bei Lagerung	0 - 15000 m

Gewicht und Abmessungen	
Breite	55 mm
Tiefe	56 mm
Höhe	1800 mm
Gewicht	6,82 kg

Verpackungsdaten	
Paketgewicht	7,99 kg
Verpackungsbreite	195 mm
Verpackungstiefe	130 mm
Verpackungshöhe	2030 mm

0731304733423

731304733423

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 21-NOV-2026. Prints or copies of Information are only valid on the printed Publication date