LogiLink

LogiLink USB-C Ladegerät, 40 W, GaN, 2-fach, 2x USB-C (PD), Weiß



Marke : LogiLink

Artikel-Code: PA0282

Produktname : USB-C Ladegerät, 40 W, GaN, 2-fach, 2x USB-C (PD), Weiß

USB-C Ladegerät, 40 W, GaN, 2-fach, 2x USB-C (PD), Weiß

LogiLink USB-C Ladegerät, 40 W, GaN, 2-fach, 2x USB-C (PD), Weiß:

Durch die eingebaute Galliumnitrid-Technologie (GaN), wird die Leistung und Ladegeschwindigkeit mit hoher Effizienz auf ein ganz neues Niveau gehoben. Das Besondere daran ist vor allem die kompakte Größe aber gleichzeitig äußerst leistungsstarke Bauweise. So macht der USB-Steckdosenadapter von LogiLink das Aufladen Ihrer USB-C-Geräte zum Kinderspiel. Außerdem unterstützt der PA0282 das PPS-Laden (Programmable Power Supply) und passt die Ausgangsleistung in Echtzeit an den Ladestatus des Geräts an, um es mit maximaler Leistung zu versorgen.
LogiLink USB-C Ladegerät, 40 W, GaN, 2-fach, 2x USB-C (PD), Weiß. Aufladetyp: Drinnen, Energiequelle: AC, Aufladekompatibilität: Handy, Tablets. Eingangsspannung: 230 - 240 V, AC-Adapter Ausgangsstrom: 1 A. USB Typ-C Anzahl Anschlüsse: 1, Schnellladung, Energieschutzeigenschaften: Überspannung, Überlast, Überhitzung, Kurzschluß. Produktfarbe: Weiß



Leistungen	
Aufladekompatibilität *	Handy, Tablets
Energiequelle *	AC
USB 3.2 Gen 1 (3.1 Gen 1) Anzahl der Anschlüsse vom Typ A	1
USB Typ-C Anzahl Anschlüsse	1
Schnellladung	✔
Aufladetyp *	Drinnen
USB Power Delivery	✔
Energieschutzeigenschaften	Überspannung, Überlast, Überhitzung, Kurzschluß

Design	
Produktfarbe *	Weiß
Galliumnitrid (GaN)-Transistoren	✔

Energie	
Eingangsspannung	230 - 240 V
Eingangsfrequenz	50/60 Hz
Max. Leistung	40 W
AC-Adapter Ausgangsstrom	1 A
Ausgangsstrom (5V)	3 A
Ausgangsstrom (9V)	2,22 A

Energie	
Ausgangsstrom (12V)	1,67 A

Gewicht und Abmessungen	
Breite	359 mm
Tiefe	925 mm
Höhe	55 mm
Gewicht	105 g

Verpackungsdaten	
Verpackungsart	Box

Betriebsbedingungen	
Betriebstemperatur	-10 - 40 °C
Temperaturbereich bei Lagerung	-20 - 80 °C
Relative Luftfeuchtigkeit in Betrieb	35 - 85%
Luftfeuchtigkeit bei Lagerung	5 - 95%

Lieferumfang	
Menge pro Packung	1 Stück(e)

Zertifikate	
Konformitätsbescheinigungen	CE

4052792067545

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 18-NOV-2026. Prints or copies of Information are only valid on the printed Publication date