APC Easy UPS On-Line, 1000VA/900W, Rackmontage 4HE, 230V, 4x IEC C13 Ausgänge, Intelligenter Kartensteckplatz, LCD, verlängerte Laufzeit, mit Rackkit

Marke : APC

Artikel-Code: SRV1KRILRK-E

Produktname : APC Easy UPS On-Line, 1000VA/900W, Rackmontage 4HE, 230V, 4x IEC C13 Ausgänge, Intelligenter Kartensteckplatz, LCD, verlängerte Laufzeit, mit Rackkit

APC Easy UPS On-Line, 1000VA/900W, Rackmontage 4HE, 230V, 4x IEC C13 Ausgänge, Intelligenter Kartensteckplatz, LCD, verlängerte Laufzeit, mit Rackkit
APC Easy UPS On-Line, 1000VA/900W, Rackmontage 4HE, 230V, 4x IEC C13 Ausgänge, Intelligenter Kartensteckplatz, LCD, verlängerte Laufzeit, mit Rackkit. Ausgangskapazität: 1 kVA, Ausgangsleistung: 900 W, Wellenform: Sine. AC-Steckertypen: C13-Koppler, Stecker: C14-Koppler. Akku-/Batterietechnologie: Plombierte Bleisäure (VRLA), Akku-/Batteriespannung: 36 V, Akkuladezeit: 4,5 h. Produktfarbe: Schwarz, Rack-Kapazität: 4U, Internationale Schutzart (IP-Code): IP20. Breite: 438 mm, Tiefe: 412 mm, Höhe: 172 mm

Merkmale	
Ausgangskapazität *	1 kVA
Ausgangsleistung *	900 W
Wellenform *	Sine
Eingangs-Betriebsspannung (min) *	105 V
Eingangs-Betriebsspannung (max) *	300 V
Eingangsfrequenz *	40 - 70 Hz
Ausgangs-Betriebsspannung (min)	230 V
Output Frequenz	50/60 Hz
Anstieg der Energiemenge	600 J
Wärmeableitung	372 BTU/h
Crest-Faktor	3:1
Geräuschpegel	50 dB
Anschlüsse und Schnittstellen	
AC-Steckertypen	C13-Koppler
Stecker	C14-Koppler
SmartSlot	✓
SmartConnect-Anschluss	✗
Akku/Batterie	
Akku-/Batterietechnologie	Plombierte Bleisäure (VRLA)
Akku-/Batteriespannung	36 V
Akkuladezeit	4,5 h
Design	
Rack-Kapazität	4U

Design	
Produktfarbe *	Schwarz
Internationale Schutzart (IP-Code)	IP20
Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-20 - 50 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Luftfeuchtigkeit bei Lagerung	0 - 95%
Höhe bei Betrieb	0 - 3000 m
Lieferumfang	
Management-Karte enthalten	✗
Gewicht und Abmessungen	
Breite	438 mm
Tiefe	412 mm
Höhe	172 mm
Gewicht	27,1 kg
Verpackungsdaten	
Verpackungsbreite	600 mm
Verpackungstiefe	500 mm
Verpackungshöhe	480 mm
Paketgewicht	33,1 kg
Logistikdaten	
Garantiezeit	2 Jahr(e)



0731304450962



731304450962



8592978631765



5715328161856



5054444905457

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 20-NOV-2026. Prints or copies of Information are only valid on the printed Publication date