APC SMT1500RMX93 Unterbrechungsfreie Stromversorgung (USV) Line-Interaktiv 1,44 kVA 1000 W 6 AC-Ausgänge



Marke : APC

Artikel-Code: SMT1500RMX93

Produktname : SMT1500RMX93



APC SMT1500RMX93. USV-Topologie: Line-Interaktiv, Ausgangskapazität: 1,44 kVA, Ausgangsleistung: 1000 W. AC-Steckertypen: NEMA 5-15R, Stecker: NEMA 5-15P, Anzahl der AC-Ausgänge: 6 AC-Ausgänge. Akku-/Batterietechnologie: Plombierte Bleisäure (VRLA), Batteriekapazität: 432 Ah, Typische Backup-Zeit bei voller Belastung: 7 min. Formfaktor: Rackmount, Produktfarbe: Schwarz, Rack-Kapazität: 0U. Konformitätsbescheinigungen: REACH, RoHS, WEEE, Zertifizierung: REACH, RoHS, WEEE, CSA C22.2 No 107.1

Merkmale	
USV-Topologie *	Line-Interaktiv
Ausgangskapazität *	1,44 kVA
Ausgangsleistung *	1000 W
Wellenform *	Sine
Eingangs-Betriebsspannung (min) *	82 V
Eingangs-Betriebsspannung (max) *	144 V
Eingangsfrequenz *	50/60 Hz
Ausgangs-Betriebsspannung (max)	120 V
Output Frequenz	50/60 Hz
Anstieg der Energiemenge	693 J
Reaktionszeit	6 ms
Geräuschpegel	45 dB
Akustische Signale	✔

Anschlüsse und Schnittstellen	
AC-Steckertypen	NEMA 5-15R
Stecker	NEMA 5-15P
Anzahl der AC-Ausgänge	6 AC-Ausgänge
USB Anschluss	✔

Akku/Batterie	
Akku-/Batterietechnologie	Plombierte Bleisäure (VRLA)
Batteriekapazität	432 Ah
Typische Backup-Zeit bei voller Belastung	7 min
Typische Backup-Zeit bei halber Belastung	26 min
Batterielebensdauer (max.)	5 Jahr(e)
Akkuladezeit	3 h

Design	
Formfaktor *	Rackmount

Design	
Rack-Kapazität	0U
Produktfarbe *	Schwarz
Steuerung	Tasten
Displaytyp	LED

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-20 - 55 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Luftfeuchtigkeit bei Lagerung	0 - 95%
Höhe bei Betrieb	0 - 3000 m
Höhe bei Lagerung	0 - 15000 m

Zertifikate	
Konformitätsbescheinigungen	REACH, RoHS, WEEE
Zertifizierung	REACH, RoHS, WEEE, CSA C22.2 No 107.1

Lieferumfang	
Betriebsanleitung	✔

Nachhaltigkeit	
Enthält nicht	Quecksilber

Gewicht und Abmessungen	
Breite	432 mm
Tiefe	477 mm
Höhe	86 mm
Gewicht	26,5 kg

Verpackungsdaten	
Verpackungsbreite	610 mm
Verpackungstiefe	590 mm
Verpackungshöhe	235 mm
Paketgewicht	26,5 kg

Logistikdaten	
Garantiezeit	3 Jahr(e)

0731304433651

731304433651

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 19-NOV-2026. Prints or copies of Information are only valid on the printed Publication date