APC GVSUPS50KB4GS Unterbrechungsfreie Stromversorgung (USV) Doppelwandler (Online) 50 kVA 50000 W

Marke : APC

Artikel-Code: GVSUPS50KB4GS

Produktname : GVSUPS50KB4GS

APC GVSUPS50KB4GS. USV-Topologie: Doppelwandler (Online), Ausgangskapazität: 50 kVA, Ausgangsleistung: 50000 W. AC-Steckertypen: Hard Wire 3-wire (3PH + G), Hard Wire 5-wire (3PH + N + G). Akku-/Batterietechnologie: Plombierte Bleisäure (VRLA), Akku-/Batteriespannung: 480 V. Formfaktor: Tower, Produktfarbe: Weiß, Displaytyp: LCD. Zertifizierung: CSA C22.2 No 107.3, FCC Part 15 class A, IEC 62040-3, IEC 60721-4-2 Level 2M2, UL 1778 5th edition

Merkmale	
USV-Topologie *	Doppelwandler (Online)
Ausgangskapazität *	50 kVA
Ausgangsleistung *	50000 W
Wellenform *	Sine
Eingangs-Betriebsspannung (max) *	480 V
Eingangsfrequenz *	40/70 Hz
Ausgangs-Betriebsspannung (max)	480 V
Output Frequenz	50/60 Hz
Stromstärke (maximal)	74 A
Wärmeableitung	5210 BTU/h
Anzahl der Eingangs-Phasen	3
Anzahl der Ausgangs-Phasen	3
Eingangs-Leistungsfaktor	0,99
Crest-Faktor	2.5:1
ECO-Modus	✔
Eingangsstrom Gesamtverzerrungsfaktor THD	3%
Geräuschpegel	61 dB
Energieschutzeigenschaften	Überlastung, Kurzschluß
Akustische Signale	✔

Anschlüsse und Schnittstellen	
AC-Steckertypen	Hard Wire 3-wire (3PH + G), Hard Wire 5-wire (3PH + N + G)
SmartSlot	✔

Akku/Batterie	
Akku-/Batterietechnologie	Plombierte Bleisäure (VRLA)
Akku-/Batteriespannung	480 V

Design	
Formfaktor *	Tower
Produktfarbe *	Weiß

Design	
Displaytyp	LCD
Internationale Schutzart (IP-Code)	IP20

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-15 - 40 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 90%
Luftfeuchtigkeit bei Lagerung	10 - 80%
Höhe bei Betrieb	0 - 1000 m
Höhe bei Lagerung	0 - 3048 m

Zertifikate	
Zertifizierung	CSA C22.2 No 107.3, FCC Part 15 class A, IEC 62040-3, IEC 60721-4-2 Level 2M2, UL 1778 5th edition

Lieferumfang	
Betriebsanleitung	✔
Schnellinstallationsanleitung	✔

Gewicht und Abmessungen	
Breite	521 mm
Tiefe	847 mm
Höhe	1485 mm
Gewicht	460 kg

Verpackungsdaten	
Verpackungsbreite	640 mm
Verpackungstiefe	990 mm
Verpackungshöhe	1680 mm
Paketgewicht	490 kg



0731304641841



731304641841

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 21-NOV-2026. Prints or copies of Information are only valid on the printed Publication date