APC Symmetra PX, 32 kW, skalierbar auf 96 kW, 400 V, mit modularer Energieverteilung





Marke : APC

Artikel-Code: SY32K96H-PD

Produktname : Symmetra PX, 32 kW, skalierbar auf 96 kW, 400 V, mit modularer Energieverteilung

Symmetra PX, 32 kW, skalierbar auf 96 kW, 400 V, mit modularer Energieverteilung
APC Symmetra PX, 32 kW, skalierbar auf 96 kW, 400 V, mit modularer Energieverteilung. Ausgangskapazität: 96 kVA, Ausgangsleistung: 96000 W, Eingangs-Betriebsspannung (min): 340 V. AC-Steckertypen: Hard Wire 5-wire (3PH + N + G). Akkuladezeit: 3,50 h. Produktfarbe: Schwarz, Displaytyp: LCD. Zertifizierung: EN 50091-1,EN/IEC 62040-3,EN/IEC 62040-1-1,FCC Part 15 Class A,VFI-SS-111

Merkmale	
Ausgangskapazität *	96 kVA
Ausgangsleistung *	96000 W
Eingangs-Betriebsspannung (min) *	340 V
Eingangs-Betriebsspannung (max) *	477 V
Eingangsfrequenz *	50/60 Hz
Ausgangs-Betriebsspannung (min)	380 V
Ausgangs-Betriebsspannung (max)	415 V
Stromstärke (maximal)	59 A
Effizienz	95%
Notstrom Aus (EPO)	✔
Ausgangsspannung Gesamtverzerrungsfaktor THD	2%
EMI/RFI Lautstärkefilter	✔
Geräuschpegel	61 dB
Energieschutzeigenschaften	Überstrom, Überlastschutz
Akustische Signale	✔
Anschlüsse und Schnittstellen	
AC-Steckertypen	Hard Wire 5-wire (3PH + N + G)
Akku/Batterie	
Akkuladezeit	3,50 h
Hot-Swap-Batterie	✔
Design	
Produktfarbe *	Schwarz
Displaytyp	LCD
Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C

Betriebsbedingungen	
Temperaturbereich bei Lagerung	-15 - 40 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Luftfeuchtigkeit bei Lagerung	0 - 95%
Höhe bei Betrieb	0 - 999,9 m
Höhe bei Lagerung	0 - 15000 m
Zertifikate	
Zertifizierung	EN 50091-1,EN/IEC 62040-3,EN/IEC 62040-1-1,FCC Part 15 Class A,VFI-SS-111
Gewicht und Abmessungen	
Breite	1200 mm
Tiefe	1070 mm
Höhe	1991 mm
Gewicht	1814 kg
Verpackungsdaten	
Paketgewicht	1963 kg
Logistikdaten	
Warentarifnummer (HS)	85078000
Sonstige Funktionen	
Anzahl der Phasen	3
Akku-/Batterietyp	VRLA
Schnittstelle	2 x SmartSlot
Nominale Ausgang Spannung	400 V
Ausgang Spannung (Note)	380: 400 / 415 V 3 Ph
Nominale Eingang Spannung	400 V
Überlastung Schutz	✔
Verpackungsabmessungen (BxTxH)	1696 x 1210 x 2140 mm

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 18-NOV-2026. Prints or copies of Information are only valid on the printed Publication date