APC Easy 3S Unterbrechungsfreie Stromversorgung (USV) Doppelwandler (Online) 15 kVA 15000 W



Marke : APC

Artikel-Code: E3SUPS15KHB1

Produktname : Easy 3S

Easy UPS 3S, 15 KWm, 15 kV, 400V 3PH, 3x VRLA, IP20, 1400x9652x928 mm
APC Easy 3S. USV-Topologie: Doppelwandler (Online), Ausgangskapazität: 15 kVA, Ausgangsleistung: 15000 W. Akku-/Batterietechnologie: Plombierte Bleisäure (VRLA), Akku-/Batteriespannung: 240 V, Typische Backup-Zeit bei voller Belastung: 9 min. Formfaktor: Tower, Produktfarbe: Weiß, Internationale Schutzart (IP-Code): IP20. Konformitätsbescheinigungen: RoHS, Zertifizierung: CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH. Breite: 9652 mm, Tiefe: 928 mm, Höhe: 1400 mm



Merkmale	
USV-Topologie *	Doppelwandler (Online)
Ausgangskapazität *	15 kVA
Ausgangsleistung *	15000 W
Wellenform *	Reiner Sinus
Eingangs-Betriebsspannung (min) *	304 V
Eingangs-Betriebsspannung (max) *	477 V
Eingangsfrequenz *	45/65 Hz
Ausgangs-Betriebsspannung (min)	380 V
Ausgangs-Betriebsspannung (max)	415 V
Output Frequenz	50/60 Hz
Stromstärke (maximal)	28 A
Anzahl der Eingangs-Phasen	3
Anzahl der Ausgangs-Phasen	3
Eingangs-Leistungsfaktor	0,99
Ausgangsspannung Gesamtverzerrungsfaktor THD	3%
Eingangsstrom Gesamtverzerrungsfaktor THD	3%
Geräuschpegel	60 dB

Anschlüsse und Schnittstellen	
SmartSlot	✔
SmartConnect-Anschluss	✘

Akku/Batterie	
Akku-/Batterietechnologie	Plombierte Bleisäure (VRLA)
Akku-/Batteriespannung	240 V
Anzahl unterstützter Akkus/Batterien	3
Typische Backup-Zeit bei voller Belastung	9 min

Design	
Produktfarbe *	Weiß
Internationale Schutzart (IP-Code)	IP20

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-15 - 40 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Luftfeuchtigkeit bei Lagerung	0 - 95%
Höhe bei Betrieb	0 - 999,9 m
Höhe bei Lagerung	0 - 15000 m

Zertifikate	
Konformitätsbescheinigungen	RoHS
Zertifizierung	CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH

Lieferumfang	
Management-Karte enthalten	✘
Schnellinstallationsanleitung	✔

Gewicht und Abmessungen	
Breite	9652 mm
Tiefe	928 mm
Höhe	1400 mm
Gewicht	436 kg

Verpackungsdaten	
Verpackungsbreite	14300 mm
Verpackungstiefe	1014 mm
Verpackungshöhe	1640 mm
Paketgewicht	481 kg

Design	
Formfaktor *	Tower

Logistikdaten	
Warentarifnummer (HS)	85078000

Sonstige Funktionen	
Ausgangsspannung	400 V



0731304428190



731304428190



8592978404765

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 20-NOV-2026. Prints or copies of Information are only valid on the printed Publication date