APC NetShelter Rack PDU Advanced, Metered, 3Phase, 43,5kW 400V 63A or 34,6kW 415V 60A, 42 Ausgänge, IEC309



Marke : APC

Artikel-Code: APDU10450ME

Produktname : APC NetShelter Rack PDU Advanced, Metered, 3Phase, 43,5kW 400V 63A or 34,6kW 415V 60A, 42 Ausgänge, IEC309

APC NetShelter Rack PDU Advanced, Metered, 3Phase, 43,5kW 400V 63A or 34,6kW 415V 60A, 42 Ausgänge, IEC309
APC NetShelter Rack PDU Advanced, Metered, 3Phase, 43,5kW 400V 63A or 34,6kW 415V 60A, 42 Ausgänge, IEC309. PDU-Typen: Geändert, Rack-Kapazität: 0U, Typ: Einphasig. Anzahl der AC-Ausgänge: 48 AC-Ausgänge, AC-Steckertypen: C13-Koppler, C15-Koppler, C19-Koppler, C21-Koppler, Stecker: IEC 60309. Nominale Eingang Spannung: 415 V, Stromstärke (maximal): 60 A, AC Eingangsfrequenz: 50 - 60 Hz. Zertifizierung: CSA C22.2 No 62368-1, FCC part 15 subpart B, UL 62368-1. Breite: 56 mm, Tiefe: 75 mm, Höhe: 1826 mm

Design	
PDU-Typen *	Geändert
Typ	Einphasig
Rack-Kapazität *	0U
Montage	Senkrecht
Produktfarbe	Schwarz
Display	LCD
Ein-/Ausschalter	✗

Anschlüsse und Schnittstellen	
Anzahl der AC-Ausgänge *	48 AC-Ausgänge
Stecker	IEC 60309
AC-Steckertypen *	C13-Koppler, C15-Koppler, C19-Koppler, C21-Koppler

Merkmale	
Verkettung	✓

Energie	
Nominale Eingang Spannung *	415 V
AC Eingangsfrequenz	50 - 60 Hz
Stromstärke (maximal) *	60 A
Nominale Ausgang Spannung	240 V
Ausgangsspannung	240 V
Ladekapazität	34600 VA
Maximaler Eingang Strom pro Phase	60 A
Maximale Gesamtstromaufnahme pro Phase	48 A

Zertifikate	
Zertifizierung	CSA C22.2 No 62368-1, FCC part 15 subpart B, UL 62368-1

Betriebsbedingungen	
Betriebstemperatur	-5 - 60 °C
Temperaturbereich bei Lagerung	-25 - 65 °C
Relative Luftfeuchtigkeit in Betrieb	5 - 95%
Luftfeuchtigkeit bei Lagerung	5 - 95%
Höhe bei Betrieb	0 - 3048 m
Höhe bei Lagerung	0 - 15240 m

Gewicht und Abmessungen	
Breite	56 mm
Tiefe	75 mm
Höhe	1826 mm
Gewicht	11,7 kg

Verpackungsdaten	
Paketgewicht	14,7 kg
Verpackungsbreite	262 mm
Verpackungstiefe	132 mm
Verpackungshöhe	1980 mm

Logistikdaten	
Gesamter Kohlendioxid-Fußabdruck (kg of CO2e)	21687,02



0731304439103



731304439103

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 21-NOV-2026. Prints or copies of Information are only valid on the printed Publication date