LogiLink

# LogiLink Steckdosenleiste 4-fach + Schalter, 4x CEE 7/3, Outdoor, 1,5 m, schwarz/gelb



**Marke :** LogiLink

**Artikel-Code:** LPS254

**Produktname :** Steckdosenleiste 4-fach + Schalter, 4x CEE 7/3, Outdoor, 1,5 m, schwarz/gelb

- 4x Schutzkontaktbuchse
- Mit beleuchtetem Ein/Aus-Schalter
- Anordnung der Buchsen im 45°-Winkel
- Buchsen mit erhöhtem Berührungsschutz
- IP44: Schutz gegen das Eindringen von festen Fremdkörpern >1 mm und Spritzwasser
- TÜV und GS zertifiziert
- Robustes Kunststoffgehäuse
- Gerader Schutzkontaktstecker
- Leistung: 230 V/16 A, 50 Hz, max. 3680 W
- Kabelspezifikation: H07RN-F 3G 1,5 mm2
- Kabellänge: 1,5 m
- Farbe: Schwarz mit gelben Klappdeckeln



Steckdosenleiste 4-fach + Schalter, 4x CEE 7/3, Outdoor, 1,5 m, schwarz/gelb

LogiLink Steckdosenleiste 4-fach + Schalter, 4x CEE 7/3, Outdoor, 1,5 m, schwarz/gelb:

Mit einer Kabellänge von 1,5m ist die LogiLink Steckdosenleiste perfekt für den Einsatz in Außenbereichen geeignet. Sie können die Leiste mit dem beleuchteten Schalter ganz einfach ein- und ausstellen um Strom zu sparen. Die LPS254 bietet Schutz vor Fremdkörpern wie grobem Sand und vor Spritzwasser (IP44) und ist somit optimal für den Einsatz in feuchten Räumen und Umgebungen.

| Merkmale | |
|---|---|
| AC-Steckertypen | Typ F |
| Kabellänge * | 1,5 m |
| Stromstecker-Typ | Type F (CEE 7/4) |
| Unterstützte Positionierung * | Draußen |
| Ein-/Ausschalter * | ✔ |
| Internationale Schutzart (IP-Code) | IP44 |
| Kerngröße | 1,5 mm² |
| Anzeigelicht | ✔ |
| Produktfarbe | Schwarz, Gelb |
| Zertifizierung | TÜV, GS, CE |
| **Anschlüsse und Schnittstellen** | |
| Anzahl der AC-Ausgänge * | 4 AC-Ausgänge |
| **Energie** | |
| AC Eingangsspannung | 230 V |

| Energie | |
|---|---|
| AC Eingangsfrequenz | 50 Hz |
| Maximale Eingangsleistung | 3680 W |
| Stromstärke (maximal) | 16 A |
| **Gewicht und Abmessungen** | |
| Breite | 75 mm |
| Tiefe | 346 mm |
| Höhe | 59,6 mm |
| **Technische Details** | |
| Konformitätsbescheinigungen | RoHS |
| **Verpackungsdaten** | |
| Anzahl enthaltener Produkte | 1 Stück(e) |
| Verpackungsbreite | 360 mm |
| Verpackungstiefe | 90 mm |
| Verpackungshöhe | 60 mm |
| Paketgewicht | 630 g |

4052792060614

**Catalog Object Cloud**

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 21-NOV-2026. Prints or copies of Information are only valid on the printed Publication date