APC SMX3000LV Unterbrechungsfreie Stromversorgung (USV) 3 kVA 2700 W 10 AC-Ausgänge





Marke : APC

Artikel-Code: SMX3000LV

Produktname : SMX3000LV

APC SMX3000LV. Ausgangskapazität: 3 kVA, Ausgangsleistung: 2700 W, Wellenform: Sine. AC-Steckertypen: NEMA 5–15R, NEMA 5–20R, NEMA L5-30R, Stecker: NEMA L5-30P, Anzahl der AC-Ausgänge: 10 AC-Ausgänge. Akku-/Batterietechnologie: Plombierte Bleisäure (VRLA), Akkuladezeit: 3 h. Formfaktor: Rackmount/Tower, Produktfarbe: Schwarz, Rack-Kapazität: 2U. Konformitätsbescheinigungen: RoHS, Zertifizierung: BSMI, CSA, EN 50091-2, EN 55022 Class A, FCC Part 15 Class A, NOM, TUV, UL 1778, VCCI Class A...

Merkmale	
Ausgangskapazität *	3 kVA
Ausgangsleistung *	2700 W
Wellenform *	Sine
Eingangs-Betriebsspannung (min) *	70 V
Eingangs-Betriebsspannung (max) *	153 V
Eingangsfrequenz *	50/60 Hz
Anstieg der Energiemenge	540 J
Effizienz	97,5%
Notstrom Aus (EPO)	✔
Ausgangsspannung Gesamtverzerrungsfaktor THD	5%
Geräuschpegel	55 dB
Akustische Signale	✔

Anschlüsse und Schnittstellen	
AC-Steckertypen	NEMA 5–15R, NEMA 5–20R, NEMA L5-30R
Stecker	NEMA L5-30P
Anzahl der AC-Ausgänge	10 AC-Ausgänge
Anzahl USB 2.0 Anschlüsse	1

Akku/Batterie	
Akku-/Batterietechnologie	Plombierte Bleisäure (VRLA)
Anzahl unterstützter Akkus/Batterien	1
Akkuladezeit	3 h

Design	
Formfaktor *	Rackmount/Tower

Design	
Rack-Kapazität	2U
Kabellänge	2,44 m
Produktfarbe *	Schwarz
LED-Anzeigen	✔

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-15 - 45 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Luftfeuchtigkeit bei Lagerung	0 - 95%
Höhe bei Betrieb	0 - 3000 m
Höhe bei Lagerung	0 - 15000 m

Zertifikate	
Konformitätsbescheinigungen	RoHS
Zertifizierung	BSMI, CSA, EN 50091-2, EN 55022 Class A, FCC Part 15 Class A, NOM, TUV, UL 1778, VCCI Class A REACH UL 1449

Gewicht und Abmessungen	
Breite	178 mm
Tiefe	483 mm
Höhe	432 mm
Gewicht	38,6 kg

Sonstige Funktionen	
Nominale Ausgang Spannung	120 V
Nominale Eingang Spannung	120 V
Ausgang Verbindungstyp	6 x NEMA 5-15R & 3 x NEMA 5-20R & 1 x NEMA L5-30R

7313042926478

0731304292647

731304292647

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 18-NOV-2026. Prints or copies of Information are only valid on the printed Publication date