APC Symmetra LX 16kVA N+1 Unterbrechungsfreie Stromversorgung (USV) 11200 W 1 AC-Ausgänge



Marke : APC

Artikel-Code: SYAF16KI

Produktname : Symmetra LX 16kVA N+1

Symmetra LX 16kVA N+1, 16 kVA, 11.2 kW, 62 dB, 116.36 kg, Schwarz/Silber

APC Symmetra LX 16kVA N+1 Unterbrechungsfreie Stromversorgung (USV) 11200 W 1 AC-Ausgänge:

APC Symmetra, 11.2 kW / 16 kVA, Eingang 230V, 400V 3PH / Ausgang 230V , Interface Port DB-9 RS-232, Smart-Slot

Inklusive: Software-CD, Dokumentations-CD, Installationsanleitung, Benutzerhandbuch, Web/SNMP Management Card



Standardlieferzeit: Normalerweise auf Lager
APC Symmetra LX 16kVA N+1. Ausgangskapazität: 16 kVA, Ausgangsleistung: 11200 W, Eingangs-Betriebsspannung (min): 155 V. Anzahl der AC-Ausgänge: 1 AC-Ausgänge. Akku-/Batterietechnologie: Plombierte Bleisäure (VRLA). Formfaktor: Tower. Sicherheit: C-tick, CE, EN 50091-1, EN 50091-2, EN 55022 Class A, EN 55024, EN 60950, GOST, IEC 60950, VDE

Merkmale	
Ausgangskapazität *	16 kVA
Ausgangsleistung *	11200 W
Eingangs-Betriebsspannung (min) *	155 V
Eingangs-Betriebsspannung (max) *	480 V
Eingangsfrequenz *	50/60 Hz
Ausgangs-Betriebsspannung (min)	220 V
Ausgangs-Betriebsspannung (max)	240 V
Effizienz	90%
Crest-Faktor	5:1
Notstrom Aus (EPO)	✔
Ausgangsspannung Gesamtverzerrungsfaktor THD	5%
Geräuschpegel	62 dB
Akustische Signale	✔
Anschlüsse und Schnittstellen	
Anzahl der AC-Ausgänge	1 AC-Ausgänge
RS-232 port	1
Akku/Batterie	
Akku-/Batterietechnologie	Plombierte Bleisäure (VRLA)
Design	
Formfaktor *	Tower

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-15 - 45 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Luftfeuchtigkeit bei Lagerung	0 - 95%
Höhe bei Betrieb	0 - 3000 m
Höhe bei Lagerung	0 - 4500 m
Safety regulation & standards	
Sicherheit	C-tick, CE, EN 50091-1, EN 50091-2, EN 55022 Class A, EN 55024, EN 60950, GOST, IEC 60950, VDE
Gewicht und Abmessungen	
Breite	483 mm
Tiefe	726 mm
Höhe	937 mm
Gewicht	116,4 kg
Verpackungsdaten	
Paketgewicht	147,7 kg
Sonstige Funktionen	
Akku-/Batterietyp	SYBT5
Abmessungen (BxTxH)	483 x 726 x 937 mm
Nominale Ausgang Spannung	230 V
Nominale Eingang Spannung	230-400 V
Verpackungsabmessungen (BxTxH)	599 x 997 x 1181 mm

0731304218920

731304218920

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 21-NOV-2026. Prints or copies of Information are only valid on the printed Publication date