APC Symmetra PX 48 kW, All-in-One, ohne Batterien, 400 V



Marke : APC

Artikel-Code: SY48K48H-PDNB

Produktname : Symmetra PX 48 kW, All-in-One, ohne Batterien, 400 V

Symmetra PX 48 kW, All-in-One, ohne Batterien, 400 V
APC Symmetra PX 48 kW, All-in-One, ohne Batterien, 400 V. USV-Topologie: Doppelwandler (Online), Ausgangskapazität: 48 kVA, Ausgangsleistung: 48000 W. Stecker: Terminal. Produktfarbe: Schwarz, Displaytyp: LCD. Zertifizierung: EN 50091-1, EN/IEC 62040-1-1, EN/IEC 62040-3, FCC Part 15 Class A, ISO 14001, ISO 9001, VFI-SS-111. Breite: 600 mm, Tiefe: 1070 mm, Höhe: 1991 mm

Merkmale	
USV-Topologie *	Doppelwandler (Online)
Ausgangskapazität *	48 kVA
Ausgangsleistung *	48000 W
Wellenform *	Sine
Eingangs-Betriebsspannung (min) *	340 V
Eingangs-Betriebsspannung (max) *	477 V
Eingangsfrequenz *	40 - 70 Hz
Ausgangs-Betriebsspannung (min)	380 V
Ausgangs-Betriebsspannung (max)	415 V
Output Frequenz	50/60 Hz
Stromstärke (maximal)	98 A
Notstrom Aus (EPO)	✔
Ausgangsspannung Gesamtverzerrungsfaktor THD	2%
Eingangsstrom Gesamtverzerrungsfaktor THD	5%
Geräuschpegel	61 dB
Akustische Signale	✔
Web-basiertes Management	✔
Akustische Alarm-Modi	Alarm bei Batteriebetrieb, Warnung bei geringer Batterie

Anschlüsse und Schnittstellen	
Stecker	Terminal
SmartSlot	✔

Design	
Produktfarbe *	Schwarz

Design	
Displaytyp	LCD
LED-Anzeigen	✔

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-15 - 40 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Luftfeuchtigkeit bei Lagerung	0 - 95%
Höhe bei Lagerung	0 - 15000 m

Zertifikate	
Zertifizierung	EN 50091-1, EN/IEC 62040-1-1, EN/IEC 62040-3, FCC Part 15 Class A, ISO 14001, ISO 9001, VFI-SS-111

Lieferumfang	
Management-Karte enthalten	✔

Gewicht und Abmessungen	
Breite	600 mm
Tiefe	1070 mm
Höhe	1991 mm
Gewicht	397 kg

Verpackungsdaten	
Service enthalten	Start-Up Service
Verpackungsbreite	848 mm
Verpackungstiefe	1210 mm
Verpackungshöhe	2140 mm
Paketgewicht	430 kg

Sonstige Funktionen	
Verpackungsinhalt	Network Management Card, Start-Up Servic

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 20-NOV-2026. Prints or copies of Information are only valid on the printed Publication date