APC Easy UPS 3S USV 15 kVA 400V 3:1 USV, 1 interner 7Ah modularer Batteriestrang, erweiterbar auf 3



Marke : APC

Artikel-Code: E3SUPS15K3IB1

Produktname : Easy UPS 3S USV 15 kVA 400V 3:1 USV, 1 interner 7Ah modularer Batteriestrang, erweiterbar auf 3

Easy UPS 3S USV 15 kVA 400V 3:1 USV, 1 interner 7Ah modularer Batteriestrang, erweiterbar auf 3

APC Easy UPS 3S USV 15 kVA 400V 3:1 USV, 1 interner 7Ah modularer Batteriestrang, erweiterbar auf 3:

Hocheffiziente dreiphasige USV mit internen Batterien. Die USV bietet modernste Funktionen, herausragende Spezifikationen und robuste Elektrik – für maximale Geschäftskontinuität im Datacenter oder Technikraum. Diese USV mit 15 kVA lässt sich leicht installieren, bedienen und warten. Sie eignet sich ideal für kleine und mittlere Unternehmen. Das System enthält Staubfilter und speziell beschichtete Leiterplatten für anspruchsvolle Raumbedingungen.

Merkmale	
USV-Topologie *	Doppelwandler (Online)
Ausgangskapazität *	15 kVA
Ausgangsleistung *	15000 W
Eingangs-Betriebsspannung (min) *	380 V
Eingangs-Betriebsspannung (max) *	415 V
Eingangsfrequenz *	45/65 Hz
Ausgangs-Betriebsspannung (min)	220 V
Ausgangs-Betriebsspannung (max)	240 V
Output Frequenz	50/60 Hz
Leistungsfaktor	0,99
Crest-Faktor	3:1
Geräuschpegel	60 dB
Anschlüsse und Schnittstellen	
AC-Steckertypen	Hardwire
Akku/Batterie	
Akku-/Batterietechnologie	Plombierte Bleisäure (VRLA)
Batteriekapazität	40 Ah
Akku-/Batteriespannung	240 V
Anzahl unterstützter Akkus/Batterien	1
Design	
Produktfarbe *	Weiß

Design	
Internationale Schutzart (IP-Code)	IP20
Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-15 - 40 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Luftfeuchtigkeit bei Lagerung	0 - 95%
Zertifikate	
Konformitätsbescheinigungen	RoHS
Zertifizierung	CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE
Gewicht und Abmessungen	
Breite	380 mm
Tiefe	907 mm
Höhe	1400 mm
Gewicht	71,2 kg
Verpackungsdaten	
Verpackungsbreite	563 mm
Verpackungstiefe	1014 mm
Verpackungshöhe	1640 mm
Paketgewicht	173 kg
Logistikdaten	
Warentarifnummer (HS)	85078000



0731304428176



731304428176



3606489697990

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 21-NOV-2026. Prints or copies of Information are only valid on the printed Publication date