LogiLink

LogiLink USB 3.0 Hub, 3x USB-A, SD/microSD-Slot, 2-in-1 Anschlusskabel, 5 Gbit/s, Silber



Marke : LogiLink

Artikel-Code: UA0445

Produktname : USB 3.0 Hub, 3x USB-A, SD/microSD-Slot, 2-in-1 Anschlusskabel, 5 Gbit/s, Silber

USB 3.0 Hub, 3x USB-A, SD/microSD-Slot, 2-in-1 Anschlusskabel, 5 Gbit/s, Silber

LogiLink USB 3.0 Hub, 3x USB-A, SD/microSD-Slot, 2-in-1 Anschlusskabel, 5 Gbit/s, Silber:

Erweitern Sie die Funktionalität Ihres Geräts im Handumdrehen mit dem LogiLink USB-C 3-Port Hub mit Kartenleser. Diese kompakte und portable Lösung ist ideal, um Ihren USB-C- oder Thunderbolt 3/4-fähigen Laptop, Ihr Smartphone oder Tablet sofort um drei USB-A-Anschlüsse sowie einen SD- und microSD-Kartenleser zu erweitern. Dank des vielseitigen 2-in-1-Anschlusskabels können Sie den Hub sowohl an modernen USB-C- als auch an herkömmlichen USB-A-Geräten anschließen.



Anschlüsse und Schnittstellen	
Hostschnittstelle *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A + Type-C
Hub-Schnittstellen *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A
USB 3.2 Gen 1 (3.1 Gen 1) Anzahl der Anschlüsse vom Typ A	4
USB 3.2 Gen 1 (3.1 Gen 1) Anzahl der Anschlüsse vom Typ C	3
Anzahl Anschlüsse *	5
Integrierter Kartenleser	✔
Kartenleser-Slot	2
Kompatible Speicherkarten	SD, MicroSD (TransFlash)
Merkmale	
Datenübertragungsrate *	5000 Mbit/s
Produktfarbe	Grau
Gehäusematerial	Aluminium
Überlastung Schutz	✔
Überstromschutz	✔
Plug & Play	✔
Energie	
Netzteiltyp	USB
Stromverbrauch (max.)	4,5 W
Eingangsspannung	5 V
Eingangsstrom	0.9 A
Systemanforderung	
Unterstützt Windows-Betriebssysteme	✔

Systemanforderung	
Unterstützt Mac-Betriebssysteme	MacOS
Unterstützte Linux-Betriebssysteme	✔
Unterstützung anderer Betriebsysteme	Android, ChromeOS, iOS, iPadOS
Gewicht und Abmessungen	
Breite	99 mm
Tiefe	23 mm
Höhe	165 mm
Gewicht	46,5 g
Verpackungsdaten	
Menge pro Packung	1 Stück(e)
Verpackungsbreite	75 mm
Verpackungstiefe	25 mm
Verpackungshöhe	138 mm
Paketgewicht	68 g
Verpackungsart	Box
Lieferumfang	
Anschlussadapter enthalten	USB Typ- C weiblich auf USB Typ-A männlich
Betriebsanleitung	✔
Betriebsbedingungen	
Betriebstemperatur	0 - 45 °C
Temperaturbereich bei Lagerung	20 - 90 °C
Technische Details	
Konformitätsbescheinigungen	CE, UKCA

4052792076790

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 20-NOV-2026. Prints or copies of Information are only valid on the printed Publication date